



Company name: _____
Address: _____

Person referent: _____
e-mail: _____
Date: _____

DOORS - DOORS OPERATOR

CO _____ CH _____ STD EN81 REI _____ UK FR F FR B FR DIN18091

Execution Slim Medium Large

Extra Travel YES NO

TYPE	SLAM HAND	Q.TY
L1S/L		
L1S/R		
L2C		
L2S/L		
L2S/R		
L3S/L		
L3S/R		
L4C		
L6C		

NOTE: SLAM SIDE VIEWED FROM LANDING

EMERGENCY RELEASE STANDARD execution on top frame, for doors complete WITH frame;
 STANDARD execution on top frame, for doors complete WITHOUT frame (frame to be manufactured by the customer)
 SPECIAL execution on panel, for doors supplied WITHOUT frame (direct fixing of the wall or door WITH frame)

SILL PROFILE YES NO

STD aluminium
 Reinforced aluminium

Iron
 Capacity up to 3000 kg (tubular)
 Capacity from 3000 kg up to 10000 kg (solid profile)

Stainless steel aisi 304
 Passenger lift
 capacity up to 3000 kg (tubular)
Capacity from 3000 kg up to 10000 kg (solid profile)

SILL SUPPORT (with punched slots) YES NO

ON DEMAND Template for doors WITHOUT frame Release for car door lock

NOTE _____

PANELS YES NO

Standard execution
 Glass&Metal execution
 Diamond glass panel execution

Prime finished
 Painted RAL colour orange peel
 Painted RAL colour smooth
 Coated with _____
 Pre-arranged to receive coating

Double plated WITH rock wool
 Double plated WITHOUT rock wool

FRAME YES NO

Prime finished
 Painted RAL colour orange peel
 Painted RAL colour smooth
 Coated with _____

Double plated WITH rock wool
 Double plated WITHOUT rock wool

STANDARD dimensions
 SPECIAL dimensions
right hand post (mm)
left hand post (mm)
top frame (mm)
frame thickness (mm)

Side posts at floor level (F2 type) for assembly on finished landing

PUSH BUTTON ...cut out: YES NO

STANDARD execution cod. n°
 SPECIAL execution (b x h mm)

dim. from cut out bottom to sill level: 900 mm
 1000 mm
 1100 mm

SPECIAL execution (see enclosed drawing)
 Welded protection box

TOE GUARD YES NO

BOTTOM SHOES YES NO

FIXING YES NO

Company name: _____
Address: _____

Person referent: _____
e-mail: _____
Date: _____

DOORS - DOORS OPERATOR










CO _____ CH _____ Extra Travel: YES NO

LINEAR D.O.S. Slim Medium Large Input STD 230Vac - 1F Input SPC 110Vac - 1F Program. PAD YES NO

SINUS D.O.S. Slim Medium Large Vac: _____ Hz: _____ LYNX 48 (DC motor 48V with regulator)

Automatic operator WITH coupling cam Semi-automatic operator WITHOUT coupling cam

STANDARD UNDERSIDE OF MOUNTING = CH + 180 mm SPECIAL (mm): _____

TYPE	SLAM HAND	Q.TY
C1S/L		
C1S/R		
C2C		
C2S/L		
C2S/R		
C3S/L		
C3S/R		
C4C		
C6C		

NOTE: SLAM SIDE VIEWED FROM LANDING

- SPECIAL EXECUTIONS**
- Semi-automatic operator with spring mechanical release on panel - landing door roller H from floor level (mm) _____
 - Semi-automatic operator with mechanical release - landing door roller H from floor level (mm) _____
(see enclosed drawing for roller driving direction, interlock position and possible sill extension)
 - SPECIAL coupling cam L-290
 - SPECIAL coupling cam L-700
 - Car door lock
 - TL JONES D100SL electronic detector
 - Fixing set for assembly between operator and sill
 - Prearr. for assembly on panels
 - SPECIAL retractable toe-guard for lifts with reduced pit

- PANELS** YES NO
- Standard execution
 - Glass&Metal execution
 - Diamond glass panel execution
 - Prime finished
 - Painted RAL colour _____ orange peel
 - Painted RAL colour _____ smooth
 - Coated with _____
 - Pre-arranged to receive coating
 - Double plated

- SILL PROFILE** YES NO
- STD aluminium
 - Reinforced aluminium
 - Iron
 - Capacity up to 3000 kg (tubular)
 - Capacity from 3000 kg up to 10000 kg (solid profile)
 - Stainless steel aisi 304
 - Passenger lift
 - capacity up to 3000 kg (tubular)
Capacity from 3000 kg up to 10000 kg (solid profile)

SILL SUPPORT (with punched slots) YES NO

TOE GUARD YES NO

BOTTOM SHOES YES NO

FIXING YES NO

NOTE _____

