

Company name: _____
Address: _____
Person referent: _____
e-mail: _____

Date: _____
Quantity: _____

MODERNIZATION LANDING DOOR

Opening direction from landing

- RIGHT } Panels
 LEF } 1 2 3 4
 CENTRAL 2* 4 6 8
- * Emergency release mechanism in panel always included

Dimensions:

mm Clear opening (CO)
mm Clear height (CL)

Type:

- Glass - Aluminium
 Full glass
 Big vision panel
 Flush vision panel
 Other

Options:

- 40/10
 50/11

Fire homologations:

- no PF
 EN 81.58 EW-60
 EN 81.58 E-120
 EN 81.58 EI-120

Claddings:

- Epoxi
 Stainless steel
 Other

Operator type

- VVVF electronic module
 Mechanical:
 direct current: 12V 24V 48V
 alternating current: 230V II 125/230V III 230/415V III

Options

- Sill support
 Supplementary sill profile
 Slam post profile
 Assembling tool
 Light cover
 Emergency release mechanism in panel

Fixing type

- Standard with fixing brackets G/L/F (see catalogue section 12)
 Special
 Attached drawing
- EN 81.21 Contact lock:
- Crouzet
 Crouzed biestable
 Schmersal biestable

NOTE